



M100 Series



M300 Series



M200 Series

M-SERIES CAMERAS

M-Series cameras enable fast integration of challenging machine vision solutions. The unique ability to mix and match color, gray-scale, ingress protected, multi imager, right angle and line scan cameras with an MX-Series processor lets you define, select and deploy the perfect imaging solution for high-speed, multi-camera machine vision inspections.

HIGHLIGHTS

- GigE compatible for easy communication to M-Series processor
- VGA to 5MP resolution, in both gray scale and color
- Camera settings fully controllable by Impact Software
- Power over Ethernet (PoE) reduces cabling complexity
- Small form factor (as little as 29 mm x 29 mm x 60 mm) enables mounting in space-constrained locations
- Right-angle camera models for added camera mounting options
- Asynchronous triggering enables each camera to independently capture images at rates up to 210 frames per second (fps)
- Trigger and strobe I/O on camera eases integration

SPECIFICATIONS

GRAY-SCALE CAMERA MODEL	COLOR CAMERA MODEL	RESOLUTION	IMAGER TYPE/ SIZE (in.)	FRAME RATE (FPS)	MOUNTING DIMENSIONS (mm)
M100	M100C	659 x 494	CCD (1/4)	100	29 x 29 x 60.3
M110	M110C	659 x 494	CCD (1/3)	90	29 x 29 x 60.3
M150	M150C	1296 x 966	CCD (1/3)	30	29 x 29 x 60.3
M180	M180C	1628 x 1236	CCD (1/1.8)	20	29 x 29 x 60.3
M200*	M200C*	659 x 494	CCD (1/3)	70	44 x 29 x 85.5
M202*	M202C*	659 x 494	CCD (1/2)	79	44 x 29 x 85.5
M205	M205C	752 x 480	CMOS (1/3)	64	44 x 29 x 85.5
M210*	M210C*	782 x 582	CCD (1/2)	55	44 x 29 x 85.5
M230*	M230C*	1034 x 779	CCD (1/3)	31	44 x 29 x 85.5
M250*	M250C*	1296 x 966	CCD (1/3)	32	44 x 29 x 85.5
M270*	M270C*	1392 x 1040	CCD (2/3)	30	44 x 29 x 85.5
M295*	M295C*	1628 x 1236	CCD (1/1.8)	28	44 x 29 x 85.5
M300*	M300C*	648 x 488	CCD (1/3)	210	44 x 29 x 98.5
M330*	M330C*	1004 x 1004	CCD (2/3)	60	44 x 29 x 98.5
M350*	M350C*	1608 x 1208	CCD (1)	35	44 x 29 x 98.5
M390*	M390C*	2448 x 2050	CCD (2/3)	17	44 x 29 x 98.5

*Right-angle models available. To order gray-scale right-angle cameras, specify Model MXXX-RA. To order color right-angle cameras, specify Model MXXXC-RA.

BENEFITS

- GigE compatible for fast integration with M-Series processors
- Compact size fits many machine configurations
- High-speed trigger input
- High-speed strobe light output
- Global shutter
- C-mount lens support
- IP30 rated housing
- CE, FCC and RoHS compliant
- Utilizes color inspection tools

Datalogic Automation Headquarters

Via Lavino, 265
40050 Monte San Pietro
Bologna - Italy
Tel. +39 051/6765611
Fax +39 051/6759324
info.automation.it@datalogic.com

Datalogic Automation Inc

Machine Vision
6301 West Old Shakopee Road
Minneapolis, MN 55438 - United States
Tel. +1-952-996-9500
Fax +1-952-996-9501
info.vision.ia@datalogic.com



The company endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct installation and use, the company can guarantee only the data indicated in the instruction manual supplied with the products.